



CALI DECKING™

BamDeck® Deck Tiles

Installation Guide

(888) 788-2254
www.CaliBamboo.com

Available Colors



SLATE



CHARCOAL



COFFEE



CARAMEL

BamDeck® Tile Composite Deck Tiles 12"L x 12"W x 0.94"H - 12 sqft/box

Decking Accessories



BRICK RED BORDER TRIM



BRICK RED CORNER TRIM



ONYX BORDER TRIM



ONYX CORNER TRIM

IMPORTANT: Pre-Installation Guidelines

Note: Decking not used for its intended purpose will not be covered under warranty. For the most up-to-date information, please visit our website at CaliBamboo.com

Installation Guidelines

The following information provided by Cali Bamboo® is intended to serve as a reference guide only. Please carefully read Cali Bamboo®'s installation, maintenance, and warranty documentation prior to installation.

Safety

Always protect yourself when operating power tools. Cali Bamboo® recommends but is not limited to the following safety equipment: Gloves, eye protection, long sleeves, pants, closed toe shoes/boots and respiratory protection.

Tools Needed

To install your BamDeck® composite decking tiles, you'll need standard woodworking tools as well as a motorized saw such as a circular, miter or table saw. When using a motorized saw it is recommended to use a carbide tipped blade. If any round cuts are needed a jig saw is recommended. A hand saw can be used but will slow down the overall install.

Prior to Installation

Before installing the deck tiles, make sure your surface is clean, smooth, flat (less than 2% grade) structurally sound and water should run away from the deck. It is always recommended to check with local building codes before installing any kind of decking material. If you are not installing the deck tiles right away make sure to store the product in a clean, flat, dry place.

Ensure all doorways and gates safely clear the height of a deck tile.

Measure the area to ensure that the final row of tiles will be at least 3" wide.

Laying Tiles

Start laying the tiles in rows and make sure they fully snap together on all four sides. If you're creating a pattern, it's a good idea to take a step back from time to time and check your progress.

Removing Tiles

If you have to remove a tile, simply grip it at the locking mechanism and lift up while holding down the surrounding tiles.

Fixing Disengaged Tiles

If for any reason one of the panels detaches from the black base, do not try to force it back together as this can damage the prongs on the base. Instead, carefully insert a flat-head screwdriver into the locking mechanism on the underside of the detached panel and bend the prong gently inward on both sides while simultaneously applying pressure until it snaps back in place.

Trimming Tiles

You can use a hand saw if a tile needs to be trimmed, but a motorized circular, chop, or jig saw with a carbide tipped blade works best. When cutting, remember that tiles cannot be less than 3 inches wide -- or the width of one panel. For curved or shaped cuts, it's a good idea to use a piece of cardboard as a guide.

Care & Maintenance

It's a good idea in general to try and keep your tiles free of debris and not drag heavy objects across them. For other care and maintenance follow the same tips recommended for BamDeck® composite decking found at calibamboo.com. Remember to hold onto any extra tiles you didn't use, just in case you ever need a replacement.

